

CARDIOBLATE[®] 68000 GENERATOR

Surgical Ablation System



Empowering the Future of Surgical Ablation

Cardioblate® 68000 Generator Surgical Ablation System

Lightweight and portable with state-of-the-art electronics and design features, the Cardioblate® Generator makes it easier than ever to safely and effectively provide surgical ablation treatment for your patients.

Effective

- Bipolar algorithm customizes energy delivery based on tissue requirements providing reliable, reproducible transmuralty you can trust.
- Provides real-time treatment information in graphical and digital formats.
- Unique audible tones and touch screen messages automatically notify the user of ablation status and transmuralty.
- Message field provides critical information during the procedure.

Easy to Use

- Touch screen operation allows for easy setting and adjustment of ablation parameters.
- Color LCD screen closes into case for storage and flips open on hinge for use at different viewing angles.
- Compact and convenient to position in the OR.
- Troubleshooting steps available via touch screen messages.

MODEL	DESCRIPTION
68000	Cardioblate® Surgical Ablation System Generator and Accessories: <ul style="list-style-type: none"> • Model 60883 Remote Control Foot Switch • Model 4807 Power Cord
60889	Cardioblate® Diagnostic Kit

The Cardioblate® 68000 Generator is designed for use with the following Medtronic Ablation Devices:

- Model 60813 Cardioblate® Surgical Ablation Pen
- Model 60814 Cardioblate® XL Surgical Ablation Pen
- Model 60831 Cardioblate® BP2 Surgical Ablation Device
- Model 60841 Cardioblate® LP Surgical Ablation Device

Caution: Federal law (USA) restricts this device to sale by or on the order of a physician.

For more information contact your local Medtronic Cardiac Surgery Sales Representative or call Customer Service toll-free at 1 (800) 328-1357.



SPECIFICATIONS CARDIOBLATE® 68000 GENERATOR

DIMENSIONS

- Size: 55x35x14 cm, 21.8x13.8x5.5 in
- Weight: 9.5 kg. / 21 lbs.

POWER SUPPLY

- 100-240 VAC, 200VA, 50-60 Hz

IMPEDANCE RANGE

12 – 500 ohms +/- 15%

POWER OUTPUT

- Monopolar Mode: 1 – 50 W
- Bipolar Mode: 15 – 40 W

World Headquarters
Medtronic, Inc.
710 Medtronic Parkway
Minneapolis, MN 55432-5604
USA
Tel: (763) 514-4000
Fax: (763) 514-4879
www.medtronic.com

Medtronic USA, Inc.
Toll-free: 1 (800) 328-2518
(24-hour technical support for
physicians and medical professionals)

UC200604055 EN
© Medtronic, Inc. 2006
All Rights Reserved
Printed in USA

HEART AND VASCULAR DISEASE • NEUROLOGICAL DISORDERS • PAIN • SPINAL DISORDERS • DIABETES
UROLOGIC DISORDERS • DIGESTIVE SYSTEM DISORDERS • EYE, EAR, NOSE AND THROAT DISORDERS

